



SPECIFICATIONS

sparkeology™

PRODUCT

DUANE

DIMENSIONS

47W x 22D x 29H
59W x 22D x 29H
71W x 22D x 29H

47W x 43.5D x 29H
59W x 43.5D x 29H
71W x 43.5D x 29H



SPECIFICATIONS

LAMINATE TOPS:

Tops shall be a 3-ply construction consisting of 0.050" High pressure laminate face, medium density particle board core, and 0.028" Balancing backer, for a nominal thickness of 1-3/16".

ABS Edge Band: the tops edges shall be externally banded with a 2mm wide by 1-3/16" high, ABS edge band.

RESIN TOPS:

Tops shall be a translucent solid resin sheet offered in a thickness of 1" (25mm). The non-hazardous material has a soft profiled edge with a slightly textured finish on all sides and edges.

Profiled Edge: the top's edges shall be profiled with a dual transitional radius to form a smooth feel.

Finish: all surfaces and edges of the resin tops receive a textured finish.

TABLE BASE:

Table bases shall be constructed of 16 gauge tube steel in conjunction with 12 gauge top plates and six machined stand-offs to float the top. The top is attached to the base by means of a precision machined, powder coated decorative insert and a 1/4-20 satin nickel, decorative head machine screw. Each table base is leveled by means of (4) 1" diameter black nylon glide with a stainless steel stem.

TROUGH:

Table trough shall be constructed of 3/16" thick and 14 gauge steel. The trough's interior is designed for cord storage and the bottom and ends are perforated for cords to drop to the floor in any location for the length of the table. The single faced table trough has two mounting positions for free standing or for against the wall applications. The double faced tables are joined together by the trough creating a cord drop down the center length of the table. The troughs are attached to the table bases by means of 1/4-20 satin nickel, decorative head machine screws.

Light assembly required.