



SPECIFICATIONS



PRODUCT

PETE - ROUND

DIMENSIONS

17" DIA x 16"H	35" DIA x 23"H	47" DIA x 16"H
23" DIA x 16"H	35" DIA x 29"H	47" DIA x 20"H
23" DIA x 20"H	35" DIA x 34"H	47" DIA x 23"H
23" DIA x 23"H	35" DIA x 40"H	47" DIA x 29"H
29" DIA x 16"H	41" DIA x 16"H	47" DIA x 34"H
29" DIA x 20"H	41" DIA x 20"H	47" DIA x 40"H
29" DIA x 23"H	41" DIA x 23"H	
29" DIA x 29"H	41" DIA x 29"H	
29" DIA x 34"H	41" DIA x 34"H	
35" DIA x 16"H	41" DIA x 40"H	
35" DIA x 20"H		



SPECIFICATIONS

LAMINATE TOPS

Tops shall be a 3-ply construction consisting of 0.050" high pressure laminate face, medium density particle-board core, and 0.028" balancing backer, for a nominal total thickness of 1-3/16".

ABS edge band: The tops' edges shall be externally banded with a 2mm wide by 1-3/16" high, ABS edge band.

RESIN TOPS:

Tops shall be a Translucent solid resin material offered in a thickness of 1.0" (25mm). The material has a soft profiled edge with a slightly textured finish on all sides and edges.


Profiled Edge: The edges of top shall be profiled with a dual transitional radius to form a smooth feel.

Finish: All surfaces and edges of the resin tops receive a textured finish.

TABLE BASES:

Table bases shall be constructed of 16 gauge spun steel to form a trumpet base with a powder coat finish. The trumpet base weldment consist of a star top plate, and a spun steel weighted base. The table base is attached to the resin table top by means of a precisionally machined, powder coated decorative insert and a ¼-20 satin nickel, decorative head machine screw. The table base is attached to the laminate table top by means of a 1" long, satin nickel decorative head lag screw. The tables are leveled by means of (5) 1 3/8" diameter black nylon glides with a stainless steel stem.

Light assembly required.




SPECIFICATIONS **sparkeology**[™]

PRODUCT

PETE - SQUARE

DIMENSIONS

17W X 17D X 16H	35W X 35D X 23H	47W X 47D X 16H
23W X 23D X 16H	35W X 35D X 29H	47W X 47D X 20H
23W X 23D X 20H	35W X 35D X 34H	47W X 47D X 23H
23W X 23D X 23H	35W X 35D X 40H	47W X 47D X 29H
29W X 29D X 16H	41W X 41D X 16H	47W X 47D X 34H
29W X 29D X 20H	41W X 41D X 20H	47W X 47D X 40H
29W X 29D X 23H	41W X 41D X 23H	
29W X 29D X 29H	41W X 41D X 29H	
29W X 29D X 34H	41W X 41D X 34H	
35W X 35D X 16H	41W X 41D X 40H	
35W X 35D X 20H		



SPECIFICATIONS

LAMINATE TOPS

Tops shall be a 3-ply construction consisting of 0.050" high pressure laminate face, medium density particle-board core, and 0.028" balancing backer, for a nominal total thickness of 1-3/16".

ABS edge band: The tops' edges shall be externally banded with a 2mm wide by 1-3/16" high, ABS edge band.

RESIN TOPS:

Tops shall be a Translucent solid resin material offered in a thickness of 1.0" (25mm). The material has a soft profiled edge with a slightly textured finish on all sides and edges.


Profiled Edge: The edges of top shall be profiled with a dual transitional radius to form a smooth feel.

Finish: All surfaces and edges of the resin tops receive a textured finish.

TABLE BASES:

Table bases shall be constructed of 16 gauge spun steel to form a trumpet base with a powder coat finish. The trumpet base weldment consist of a star top plate, and a spun steel weighted base. The table base is attached to the resin table top by means of a precisionally machined, powder coated decorative insert and a ¼-20 satin nickel, decorative head machine screw. The table base is attached to the laminate table top by means of a 1" long, satin nickel decorative head lag screw. The tables are leveled by means of (5) 1 3/8" diameter black nylon glides with a stainless steel stem.

Light assembly required.




SPECIFICATIONS **sparkeology**[™]

PRODUCT

PETE - RECTANGLE

DIMENSIONS

47W X 23D X 16H	59W X 35D X 29H	83W X 47D X 29H
47W X 23D X 20H	59W X 35D X 34H	83W X 47D X 34H
47W X 23D X 23H	59W X 35D X 40H	83W X 47D X 40H
59W X 29D X 16H	71W X 41D X 16H	
59W X 29D X 20H	71W X 41D X 20H	
59W X 29D X 23H	71W X 41D X 23H	
59W X 29D X 29H	71W X 41D X 29H	
59W X 35D X 16H	83W X 47D X 16H	
59W X 35D X 20H	83W X 47D X 20H	
59W X 35D X 23H	83W X 47D X 23H	



SPECIFICATIONS

LAMINATE TOPS

Tops shall be a 3-ply construction consisting of 0.050" high pressure laminate face, medium density particle-board core, and 0.028" balancing backer, for a nominal total thickness of 1-3/16".

ABS edge band: The tops' edges shall be externally banded with a 2mm wide by 1-3/16" high, ABS edge band.

RESIN TOPS:

Tops shall be a Translucent solid resin material offered in a thickness of 1.0" (25mm). The material has a soft profiled edge with a slightly textured finish on all sides and edges.

Profiled Edge: The edges of top shall be profiled with a dual transitional radius to form a smooth feel.

Finish: All surfaces and edges of the resin tops receive a textured finish.

TABLE BASES:

Table bases shall be constructed of 16 gauge spun steel to form a trumpet base with a powder coat finish. The trumpet base weldment consist of a star top plate, and a spun steel weighted trumpet base. The table base is attached to the resin table top by means of a precisionally machined, powder coated decorative insert and a 1/4-20 satin nickel, decorative head machine screw. The table base is attached to the laminate table top by means of a 1" long, satin nickel decorative head lag screw. The tables are leveled by means of (5) 1 3/8" diameter black nylon glides with a stainless steel stem.

Light assembly required.